



**ROSE RIVER**  
EXPORT COMPANY



11721 East Cox Road, Kingman, AZ. 86401 (928) 757-5976  
Email: [bill@rosriverexportco.com](mailto:bill@rosriverexportco.com) Visit us online at [www.rosriverexportco.com](http://www.rosriverexportco.com)

# Roofing Felt



**WARRIOR<sup>®</sup> ROOFING**  
MANUFACTURING

*"We Cover America"*



Warrior Roofing 15ASTM



Warrior Roofing 15W



Warrior Roofing 30ASTM



Warrior Roofing 30W



# ROSE RIVER EXPORT COMPANY

11721 East Cox Road  
Kingman, AZ. 86401  
Email: [bill@roseriverexportco.com](mailto:bill@roseriverexportco.com)  
Phone: (928) 757-5976  
Website: [www.roseriverexportco.com](http://www.roseriverexportco.com)



## WARRIOR ROOFING MANUFACTURING SPECIFICATIONS

### # 15 ASTM

Our #15 ASTM asphalt saturated organic felt is manufactured to meet or exceed the following :

**ASTM – D226, Type 1 - Commonly called N. 15 Asphalt Felt**

**AND AS A PREPARED ROOFING ACCESSORY CLASSIFIED BY U.L. LABORATORIES AS TO EXTERNAL FIRE EXPOSURE ONLY.**

Dimensions and specifications of No. 15 ASTM asphalt felt are :

- Width of roll :** 36" + or - .7%
- Area :** 432 sq. ft.
- Net mass of saturated felt :** 11.5 lbs./100 sq. ft.
- Net mass of saturant :** 6.2 lbs./100 sq. ft.
- Saturant Weight :** Shall not be less than 1.2 times the weight of the moisture free felt.
- Saturant efficiency :** Shall be no less than 70% for type 15 asphalt saturated felt.
- Packaging :** The rolls are wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.

**Important: Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval Code # is FL 2346.**



# ROSE RIVER EXPORT COMPANY

11721 East Cox Road  
Kingman, AZ. 86401  
Email: [bill@rosriverexportco.com](mailto:bill@rosriverexportco.com)  
Phone: (928) 757-5976  
Website: [www.rosriverexportco.com](http://www.rosriverexportco.com)



## WARRIOR ROOFING MANUFACTURING

### SPECIFICATIONS

# # 15 W

Our #15W asphalt saturated organic felt is manufactured to meet or exceed the following :

**ASTM – D4869, Type I**

**AND AS A PREPARED ROOFING ACCESSORY CLASSIFIED BY U.L. LABORATORIES AS TO EXTERNAL FIRE EXPOSURE ONLY.**

Dimensions and specifications of No. 15W asphalt felt are :

**Width of roll :** 36" + or - .7%

**Area :** 432 sq. ft.

**Net mass of saturated felt :** 8.0 lbs./100 sq. ft.

**Net mass of saturant :** 4.0 lbs./100 sq. ft.

**Saturant Weight :** Shall not be less than 1.0 times the weight of the moisture free felt.

**Saturant efficiency :** Shall be no less than 75% for type 15 asphalt saturated felt.

**Packaging :** The rolls are wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.



# ROSE RIVER EXPORT COMPANY

11721 East Cox Road  
Kingman, AZ. 86401  
Email: [bill@rosriverexportco.com](mailto:bill@rosriverexportco.com)  
Phone: (928) 757-5976  
Website: [www.rosriverexportco.com](http://www.rosriverexportco.com)



## WARRIOR ROOFING MANUFACTURING SPECIFICATIONS

### # 30 ASTM

Our #30 ASTM asphalt saturated organic felt is manufactured to meet or exceed the following :

ASTM – D226, Type II - Commonly called No. 30 Asphalt Felt

FED SPECIFICATION - HHR - 595B, TYPE 30

U.L. SPECIFICATION - U.L. STANDARD 55A FOR TYPE 30 ASPHALT SATURATED ORGANIC FELT

Dimensions and specifications of No. 30 ASTM asphalt felt are :

<b>Width of roll :</b>	36" + or - .7%
<b>Area :</b>	216 sq. ft.
<b>Net mass of saturated felt :</b>	26.0 lbs./100 sq. ft.
<b>Net mass of saturant :</b>	15.0 lbs./100 sq. ft.
<b>Saturant Weight :</b>	Shall not be less than 1.5 times the weight of the moisture free felt.
<b>Saturant efficiency :</b>	Shall be no less than 70% for type 30 asphalt saturated felt.
<b>Packaging :</b>	The rolls are wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.

**Important: Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval Code # is FL 2346. Per Florida Building Code 1517.4.1 this product is marked with a yellow line signifying compliance with High Velocity Hurricane Zone requirements.**



# ROSE RIVER EXPORT COMPANY

11721 East Cox Road  
Kingman, AZ. 86401  
Email: [bill@rosriverexportco.com](mailto:bill@rosriverexportco.com)  
Phone: (928) 757-5976  
Website: [www.rosriverexportco.com](http://www.rosriverexportco.com)



## WARRIOR ROOFING MANUFACTURING SPECIFICATIONS

### # 30 W

Our #30W asphalt saturated organic felt is manufactured to meet or exceed ASTM-D4869, Type II

**Width of roll :** 36" + or - .7%

**Area :** 216 sq. ft.

**Net mass of saturated felt :** 8.0 lbs./100 sq. ft.

**Net mass of saturant :** 4.0 lbs./100 sq. ft.

**Saturant Weight :** Shall not be less than 1.0 times the weight of the moisture free felt.

**Saturant efficiency :** Shall be no less than 75% for type 30 asphalt saturated felt.

**Packaging :** The rolls are wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.

**Important: Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval Code # is FL 2346.**